

LMB 系列

LMB_LU	Ball (inch)	规格保持器				球直径				公差				主要尺寸及公差										离心率		径向游隙 (CAG)		动态/静态								
		Weight(Kg)	LMB_LU-AJ	Ball (inch)	Weight(Kg)	LMB_LU-OP	Ball (inch)	Weight(Kg)	Inch	mm	mm	Precision(Inch)	Precision(gm)	High(Inch)	High(gm)	D(Inch/mm)	D Tolerance (inch)	D Tolerance (gm)	L Tolerance (inch)	L Tolerance (gm)	B Tolerance (inch)	B Tolerance (gm)	W(Inch/mm)	D1(Inch/mm)	h(Inch/mm)	h1(Inch/mm)	θ	Precision	High	Dynamic	Static					
LMB8U	4	14	LMB8U-AJ	4	13.5	—	—	3.8	9.525	0.375	9.525	0.00025	0.4	0.00040	0.9	825015.875	0.00050	0.13	875022.225	0.0008	0.200	835816.15	0.0008	0.200	83900.992	588014.935	.041	—	—	.00038	0.00512	-.00013	225	314		
LMB8U	4	37	LMB8U-AJ	4	36.5	LMB8U-OP	3	28	1/2	12.7	0.5	12.7	0.00025	0.4	0.00040	0.9	875022.225	0.00050	0.13	1.250031.750	0.0008	0.200	962504.46	0.0008	0.200	04591.168	820920.853	.061.5	—	347.9375	80°	.00038	0.00512	-.00013	510	784
LMB8	4	8	LMB8-AJ	4	7.5	—	—	1.4	6.35	0.25	6.35	0.00025	0.4	0.00040	0.9	500012.700	0.00045	0.11	750019.050	0.0008	0.200	511012.98	0.0008	0.200	03900.992	460771.906	.041	—	—	.00038	0.00512	-.00013	206	285		
LMB10U	4	76	LMB10U-AJ	4	74	LMB10U-OP	3	57	5/8	15.875	0.625	15.875	0.00025	0.4	0.00040	0.9	1120028.375	0.00050	0.13	1.500028.100	0.0008	0.200	1121928.84	0.0008	0.200	05591.422	1.699026.899	.061.5	—	3750.525	80°	.00038	0.00512	-.00013	774	1180
LMB12U	5	95	LMB12U-AJ	5	93	LMB12U-OP	4	76	3/4	19.05	0.75	19.05	0.00030	0.7	0.00040	0.18	31.7501.250	0.00055	0.16	3.425041.275	0.0008	0.200	3.65709.81	0.0008	0.200	05591.422	1.790029.870	.061.5	—	4370.1125	50°	00040	0.00615	-.00023	801.54	862
LMB14U	6	200	LMB14U-AJ	6	198	LMB14U-OP	5	170	1	25.4	1	25.4	0.00030	0.7	0.00040	0.10	39.6881.5625	0.00065	0.16	3.250057.150	0.0012	0.300	3.747474.57	0.0012	0.300	06791.737	1.468707.306	.061.5	—	5210.13875	50°	00040	0.00615	-.00023	801.54	862
LMB20U	6	440	LMB20U-AJ	6	430	LMB20U-OP	5	370	1-1/4	31.75	1.25	31.75	0.00035	0.8	0.00050	0.12	50.80002.0000	0.00075	0.19	2.625096.675	0.0012	0.300	2.984750.92	0.0012	0.300	06791.737	1.885047.904	1.02.5	—	6210.1875	50°	000512	0.00820	-.00038	1570	2740
LMB24U	6	670	LMB24U-AJ	6	660	LMB24U-OP	5	570	1-1/2	38.1	1.5	38.1	0.00035	0.8	0.00050	0.12	60.32502.3750	0.00075	0.19	3.000076.200	0.0012	0.300	2.411861.26	0.0012	0.300	08502.184	2.238096.870	1.02.5	—	7510.65	50°	000512	0.00820	-.00038	2180	4020
LMB32U	6	1140	LMB32U-AJ	6	1120	LMB32U-OP	5	980	2	50.8	2	50.8	0.00035	0.8	0.00050	0.12	76.20003.0000	0.00090	0.22	4.0000101.600	0.0012	0.300	3.1917881.07	0.0012	0.300	10292.616	2.837072.085	1.02.5	—	1.025.40	50°	000717	0.01025	-.0005.13	3820	7940