

# LMB...UU..OP 系列

LMB...UU..OP	Ball (inch)	Ball Weight(Kg)	规格保持器		球直径		主要尺寸及公差										离心率		径向游隙 (Max)		动态静态														
			LMB...UU-AJ	LMB...UU-OP	Ball (inch)	Ball Weight(Kg)	Inch	mm	mm	Precision(Inch)	Precision(gm)	High(Inch)	High(gm)	D(Inch/mm)	D Tolerance (inch)	D Tolerance (gm)	L Tolerance(Inch)	L Tolerance(gm)	B Tolerance(Inch)	B Tolerance(gm)	W(Inch/mm)	D1(Inch/mm)	h(Inch/mm)	h1(Inch/mm)	θ	Precision	High	Dynamic	Static						
LMB4	4	8	LMB4-AJ	4	7.5	—	—	1/4	6.35	0.25	6.35	0.00025	0.4	0.00040	0.9	300012.700	0.00041	0.11	7500/19.050	0.008	0.200	5116/12.98	0.008	0.200	0.030/0.992	4687/11.906	.041	—	—	.00038	0.00512	-.00013	206	265	
LMB6UU	4	14	LMB6UU-AJ	4	13.5	—	—	3/8	9.525	0.375	9.525	0.00025	0.4	0.00040	0.9	6250/15.875	0.00050	0.13	8750/22.225	0.008	0.200	6358/16.15	0.008	0.200	0.030/0.992	5880/14.935	.041	—	—	.00038	0.00512	-.00013	225	314	
LMB8UU	4	37	LMB8UU-AJ	4	36.5	LMB8UU-OP	3	28	1/2	12.7	0.5	12.7	0.00025	0.4	0.00040	0.9	8750/22.225	0.00050	0.13	12500/31.750	0.008	0.200	9625/24.46	0.008	0.200	0.030/0.992	6450/16.51	.041	—	—	.00038	0.00512	-.00013	510	784
LMB10UU	4	76	LMB10UU-AJ	4	74	LMB10UU-OP	3	57	5/8	15.875	0.625	15.875	0.00025	0.4	0.00040	0.9	11250/28.375	0.00050	0.13	15000/38.100	0.008	0.200	11230/28.64	0.008	0.200	0.030/0.992	6590/16.74	.041	—	—	.00038	0.00512	-.00013	774	1180
LMB12UU	5	95	LMB12UU-AJ	5	93	LMB12UU-OP	4	76	3/4	19.05	0.75	19.05	0.00030	0.7	0.00040	0.18	31750/80.250	0.00050	0.16	37500/95.250	0.008	0.200	37500/95.250	0.008	0.200	0.030/0.992	6750/17.145	.041	—	—	.00040	0.00625	-.00015	862	1270
LMB14UU	6	200	LMB14UU-AJ	6	198	LMB14UU-OP	5	170	1	25.4	1	25.4	0.00030	0.7	0.00040	0.10	39680/100.25	0.00050	0.16	47500/120.25	0.012	0.300	47500/120.25	0.012	0.300	0.030/0.992	7000/17.78	.041	—	—	.00040	0.00625	-.00015	980	1570
LMB20UU	6	440	LMB20UU-AJ	6	430	LMB20UU-OP	5	370	1-1/4	31.75	1.25	31.75	0.00035	0.8	0.00050	0.12	50800/129.00	0.00075	0.19	61250/155.75	0.012	0.300	61250/155.75	0.012	0.300	0.030/0.992	8000/20.32	.041	—	—	.00040	0.00625	-.00015	1570	2740
LMB24UU	6	670	LMB24UU-AJ	6	660	LMB24UU-OP	5	570	1-1/2	38.1	1.5	38.1	0.00035	0.8	0.00050	0.12	60325/153.25	0.00075	0.19	72500/184.25	0.012	0.300	72500/184.25	0.012	0.300	0.030/0.992	8500/21.59	.041	—	—	.00040	0.00625	-.00015	1840	3200
LMB32UU	6	1	LMB32UU-AJ	6	1120	LMB32UU-OP	5	980	2	50.8	2	50.8	0.00035	0.8	0.00050	0.12	76200/193.00	0.00090	0.22	91000/230.25	0.012	0.300	91000/230.25	0.012	0.300	0.030/0.992	10000/25.4	.041	—	—	.00040	0.00625	-.00015	3820	7940